

FILE NOTATIONS

Entered in NID File

Prin. OGC

Checked by Chief

Entered On S R Sheet

Copy NID to Field Office

Location Map Pinned

Approval Letter

Card Indexed

Disapproval Letter

IWR for State or Fee Land

COMPLETION DATA:

Date Well Completed *5-28-61*

Location Inspected

✓ OGC

OW _____ WW _____ TA _____

Bond released

GW _____ OS _____ PA *✓*

State of Fee Land

8-11-61

LOGS FILED

Driller's Log *2-11-58*

Electric Logs (No.) *None*

E _____ I _____ E-I _____ GR _____ G.N. _____ Micro _____

Lat. _____ Mi-L _____ Sonic _____ Other s. _____

9-23-93

N

January 27, 1958

Black Gold and Mines Corporation
184 East 5th North
Provo, Utah

Gentlemen:

This is to acknowledge receipt of your notice of intention to re-work well No Bullock 1, which is located 30 feet from the north line and 300 feet from the west line of the ¹/₄ SE ¹/₄ of Section 22, Township 41 South, Range 12 West, SEEM, Washington County, Utah.

Please be advised that approval to drill said well is hereby granted.

Please take note that should it become necessary to plug and abandon said well you are hereby requested to give advance notice of the date and time said plugging will take place to one of the following named individuals by phone or otherwise, in order that our petroleum engineer may be present to inspect the manner in which the well is being plugged.

C. A. HANFTMAN, Petroleum Engineer

Office phone: DA 2-4721, Ext. 438

Home phone: EM 4-6790

C. B. FREIGHT, Office phone: DA 2-4721, Ext. 438

Home phone: EL 5-3629

Address all other forms of communication to the Oil & Gas Conservation Commission, Room 140, State Capitol Building, Salt Lake City, Utah.

Yours very truly,

OIL & GAS CONSERVATION COMMISSION

GILSON B. FREIGHT
SECRETARY

CBF:en

January 27, 1958

Black Gold and Mines Corporation
184 East 5th North
Provo, Utah

Gentlemen:

This is to acknowledge receipt of your notice of intention to re-work well No Bullock 1, which is located 30 feet from the north line and 300 feet from the west line of the $\frac{1}{4}$ SE $\frac{1}{4}$ of Section 22, Township 41 South, Range 12 West, 51PM, Washington County, Utah.

Please be advised that approval to drill said well is hereby granted.

Please take note that should it become necessary to plug and abandon said well you are hereby requested to give advance notice of the date and time said plugging will take place to one of the following named individuals by phone or otherwise, in order that our petroleum engineer may be present to inspect the manner in which the well is being plugged.

C. A. HAUPTMAN, Petroleum Engineer

Office phone: DA 2-4721, Ext. 438

Home phone: MM 4-6790

C. B. FREIGHT, Office phone: DA 2-4721, Ext. 438

Home phone: EL 5-3629

Address all other forms of communication to the Oil & Gas Conservation Commission, Room 140, State Capitol Building, Salt Lake City, Utah.

Yours very truly,

OIL & GAS CONSERVATION COMMISSION

OLEON B. FREIGHT
SECRETARY

CBF:cn

STATE OF UTAH
OIL & GAS CONSERVATION COMMISSION

State Capitol Building
Salt Lake City 14, Utah

REPORT OF OPERATIONS AND WELL STATUS REPORT

7-11
10-23

State Utah County Washington Field or Lease Virgin

The following is a correct report of operations and production (including drilling and producing wells) for

April, 1958

Agent's address 2585 Fillmore Ave Company Black Salt & Mines Corp.

Ogden, Utah

Signed John W. Garbath

Phone Ex. 31232

Agent's title Supt of Oil Development

State Lease No. _____ Federal Lease No. _____ Indian Lease No. _____ Fee & Pat. ☒


Sec. & 1/4 of 1/4	Temp.	Range	Well No.	Status	Oil Bbls.	Water Bbls.	Gas MCF's	REMARKS (If drilling, Depth; if shut down, Cause; Date & Results of Water Shut-Off Test; Contents of Gas; and Gas-Oil Ratio Test)
SE 1/4 SW 1/4	22	415	12W	1				Shut down to make arrangements for Rotary rig. T.D. 1405' 119' of 10" csg

NOTE: Report on this form as provided for in Rule 62. (See back of form.)

STATUS: F-Flowing P-Pumping GL-Gas Lift
SI-Shut In D-Dead
GI-Gas Injection TA-Temp. Aban.
WI-Water Injection

FILE IN DUPLICATE

Sec 22, T 41 S R 12 W



STATE OF UTAH

OIL & GAS CONSERVATION COMMISSION

STATE CAPITOL BUILDING
SALT LAKE CITY 14, UTAH

Fee and Patented.....☒
State☐
Lease No.
Public Domain☐
Lease No.
Indian☐
Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

Notice of Intention to Drill.....		Subsequent Report of Water Shut-off.....	
Notice of Intention to Change Plans.....		Subsequent Report of Altering Casing.....	
Notice of Intention to Redrill or Repair.....	X	Subsequent Report of Redrilling or Repair.....	
Notice of Intention to Pull or Alter Casing.....		Supplementary Well History.....	
Notice of Intention to Abandon Well.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

....., 19.....
Bullock
Well No. 1..... is located 30 ft. from {N} line and 300 ft. from {E} line of Sec. 22 S₁ SE₁
Sec. 22..... 41 S..... 12 W..... S. L. M.
(¼ Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Virgin..... Washington..... Utah
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3550 feet.

A drilling and plugging bond has been filed with State of Utah, Oil and Conservation Commission

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important work, surface formation, and date anticipate spudding-in.)

10 inch
The depth of this well is approximately 488 feet. Surface/pipe is cemented to a dept of 119 feet. 9 inch hole extended to 488 feet. We propose to extend this hole to 1200 feet. At the present time this hole is capped with steel cap

I understand that this plan of work must receive approval in writing by the Commission before operations may be commenced.

Company Black Gold and Mines Corporation

Address 18 1/2 East 5th, North Street

Provo, Utah

By Ben H. Bullock

Title President

INSTRUCTIONS: A plat or map must be attached to this form showing the location of all leases, property lines, drilling and producing wells, within an area of sufficient size so that the Commission may determine whether the location of the well conforms to applicable rules, regulations and orders.

LOCATE WELL CORRECTLY

STATE OF UTAH
OIL & GAS CONSERVATION COMMISSION

State Capitol Building
Salt Lake City 14, Utah

To be kept Confidential until Sept 10, 1958
(Not to exceed 4 months after filing date)

LOG OF OIL OR GAS WELL

Operating Company Black Gold Mines Corp Address 184 E. 5th North Provo, Utah
Lease or Tract: Virgin Townsite Field Virgin State Utah
Well No. 1 Sec. 22 T. 41S R. 12W Meridian Washington County Utah
Location _____ ft. $\left\{ \begin{array}{l} \text{N.} \\ \text{S.} \end{array} \right\}$ of _____ Line and _____ ft. $\left\{ \begin{array}{l} \text{E.} \\ \text{W.} \end{array} \right\}$ of _____ Line of _____ Elevation _____
(Derrick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed

Gen. H. G. Quirk

Date May 10, 1958Title President

The summary on this page is for the condition of the well at above date.

Commenced drilling March 29, 1958 Finished drilling May 7, 1958

OIL OR GAS SANDS OR ZONES

(Denote gas by G)

No. 1, from _____ to _____ No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from _____ to _____ No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	

MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth set _____

Adapter—Material _____

Size _____

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth set _____

Adapters—Material _____ Size _____

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

Cable tools were used from 488 feet to 1402 feet, and from _____ feet to _____ feet

DATES

_____, 19____ Put to producing _____, 19____

The production for the first 24 hours was _____ barrels of fluid of which _____% was oil; _____% emulsion; _____% water; and _____% sediment. Gravity, °Bé. _____

If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____

Rock pressure, lbs. per sq. in. _____

EMPLOYEES

Claude Walters, DrillerGeo. M. Arthur, Contr., Driller

_____, Driller

_____, Driller

FORMATION RECORD

FROM—	TO—	TOTAL FEET	FORMATION
488	605	117	Hard sandy, gray lime
605	657	52	Hard fine gray sand.
657	670	13	Hard, coarse bluff colored sand.
670	684	14	Dark shale.
684	692	8	Blue shale
692	715	23	Dark shale
715	730	15	Hard gray lime
730	756	26	Blue shale with gypsum
756	760	4	Hard blue lime
760	778	18	Hard, dark shale
778	803	26	Light blue shale, gypsum
803	825	22	Hard gray sand, pyrites.
825	832	7	gray sand, gypsum
832	854	22	Dark gray, sandy lime.
854	867	13	Light gray, sandy lime
867	895	28	Hard, light gray lime.
895	907	12	Blue shale
907	922	15	Hard, light gray lime
922	932	10	Sandy lime
932	945	13	Sandy lime, gypsum
945	957	12	light gray sandy lime
957	977	20	Dark shale
977	985	8	Brown shale
985	995	10	light gray, sandy shale
995	1005	10	gray shale

[OVER]

JUN 11 1958

FORMATION RECORD—Continued

FROM—	TO—	TOTAL FEET	FORMATION
1005	1037	32	Gray, sandy lime
1037	1120	83	Light gray shale, with inter- mittent, narrow layers of sand.
1120	1130	10	Hard light gray sand.
1130	1181	51	Light blue shale
1181	1193	12	Sandy lime
1193	1222	29	Hard sandy lime
1222	1281	59	Porous sand with narrow, intermittent beds of gray shale.
1281	1325	44	Dark gray to blue shale
1325	1402	77	fine, porous, fine gray to buff sand.

BOB G. HUNTER & ASSOCIATES

INVESTIGATORS • ADJUSTERS

3180 West 6th Street
Los Angeles 5, California
DUnkirk 5-2274

September 23, 1958

The State of Utah
Oil & Gas Conservation Commission
Salt Lake City 14, Utah

Attention: Cleon B. Feight, Secretary

Gentlemen:

In answer to our inquiry made your office under date of June 4th, 1958, you informed us that Black Gold & Mines Corporation, and Ben Bullock, et al, had applied for and obtained approval of the Commission in the S $\frac{1}{2}$ of SE $\frac{1}{4}$ of Sec. 22 Township 41 South Range 12 West SLBM Washington County which was previously abandoned by Mr. Bullock in 1938.

With reference to the above well, it is our understanding that under your rules, that well logs be filed with your Commission regarding well drilling operations.

If such information is filed with your Commission we would appreciate learning the depth of the well at time of abandonment, the date of approval for reentry, as well as the dates and the depth of drilling done since then.

Very truly yours,

Bob G. Hunter
BOB G. HUNTER

BGH/1h

TD 488
10" Super pipe cemented to 119' 9' and
extending to 488 feet

BOB G. HUNTER & ASSOCIATES

INVESTIGATORS • ADJUSTERS

3180 West 6th Street
Los Angeles 5, California
DUnkirk 5-2274

September 23, 1958

The State of Utah
Oil & Gas Conservation Commission
Salt Lake City 14, Utah

Attention: Cleon B. Feight, Secretary

Gentlemen:

In answer to our inquiry made your office under date of June 4th, 1958, you informed us that Black Gold & Mines Corporation, and Ben Bullock, et al, had applied for and obtained approval of the Commission in the S $\frac{1}{2}$ of SE $\frac{1}{4}$ of Sec. 22 Township 41 South Range 12 West SLBM Washington County which was previously abandoned by Mr. Bullock in 1938.

With reference to the above well, it is our understanding that under your rules, that well logs be filed with your Commission regarding well drilling operations.

If such information is filed with your Commission we would appreciate learning the depth of the well at time of abandonment, the date of approval for reentry, as well as the dates and the depth of drilling done since then.

Very truly yours,

Bob G. Hunter
BOB G. HUNTER

BGH/lh

TD 488
10" surface pipe cemented to 119' 9' depth
extending to 488 feet

September 25, 1958

Bob G. Hunter & Associates,
Investigators & Adjusters
3180 West 6th Street
Los Angeles 5, California

Re: Black Gold & Mines Corporation-
Well No. Bullock 1

Gentlemen:

With reference to your letter of September 3, 1958, please be advised that the above mentioned well was drilled prior to the establishment of this Commission. However, insofar as we can determine, said well was originally drilled to a total depth of 488 feet. There is 119 feet of 10 inch surface pipe cemented from top to bottom; from there on there is a 9 inch open hole extending to the total depth (488').

On January 27, 1958, this office approved a notice of intention to re-work said well. At that time it was proposed to extend the well depth 1200 feet. Reports filed with this office indicate that this well has been shut down since April, 1958, pending negotiations for a rotary rig.

A well log has been filed by Black Gold & Mines but we are not at liberty to release any information contained therein until after October 11, 1958, at which time the period for which said information must be kept confidential will have expired.

Yours very truly,

OIL & GAS CONSERVATION COMMISSION

CLEON B. FEIGHT
SECRETARY

CBF:co

September 25, 1958

Bob G. Hunter & Associates,
Investigators & Adjusters
3180 West 6th Street
Los Angeles 5, California

Re: Black Gold & Mines Corporation-
Well No. Bullock 1

Gentlemen:

With reference to your letter of September 3, 1958, please be advised that the above mentioned well was drilled prior to the establishment of this Commission. However, insofar as we can determine, said well was originally drilled to a total depth of 488 feet. There is 119 feet of 10 inch surface pipe cemented from top to bottom; from there on there is a 9 inch open hole extending to the total depth (488').

On January 27, 1958, this office approved a notice of intention to re-work said well. At that time it was proposed to extend the well depth 1200 feet. Reports filed with this office indicate that this well has been shut down since April, 1958, pending negotiations for a rotary rig.

A well log has been filed by Black Gold & Mines but we are not at liberty to release any information contained therein until after October 11, 1958, at which time the period for which said information must be kept confidential will have expired.

Yours very truly,

OIL & GAS CONSERVATION COMMISSION

CLEON B. FRIGHT
SECRETARY

CBF:co

BOB G. HUNTER & ASSOCIATES

INVESTIGATORS • ADJUSTERS

3180 West 6th Street
Los Angeles 5, California
DUnkirk 5-2274

October 20, 1958

The State of Utah
Oil & Gas Conservation Commission
Salt Lake City 14, Utah

Re: Black Gold & Mines Corp.,

Attention: Cleon B. Feight, Secretary

Gentlemen:

It is our understanding that we may obtain the well logs for the following described well.

Bullock #1
S $\frac{1}{2}$ of SE $\frac{1}{4}$ of Sec. 22 Township 41 Range 12
West SLBM Washington County, Utah.

We are interested in learning the depth of the well at the time of abandonment in 1938, the date of approval for reentry, as well as the dates and the depth of drilling done since then.

We are advised the logs are obtainable as of October 11, 1938, if there is a charge for same will you please advise.

Thanking you for your attention to this matter, we remain,

Very truly yours,

Bob G. Hunter
10/24

BOB G. HUNTER

BGH/lh

m-B. Coy EL 98766 - Joanne Co

October 21, 1958

Bob G. Hunter & Associates
Investigators - Adjusters
3180 West 6th Street
Los Angeles 5, California

Re: Black Gold & Mines - Well No.
Bullock 1, S $\frac{1}{2}$ SE $\frac{1}{4}$ Section 22,
Township 41 South, Range 12 West,
SLEM, WASHINGTON COUNTY..

Gentlemen:

With reference to your letter of October 20, 1958, herewith is a copy of the well log which was filed by the Black Gold & Mines Corporation on the above mentioned well.

This commission does not have any other logs, with respect to this well.

Yours very truly,

OIL & GAS CONSERVATION COMMISSION

CLEON B. FREIGHT
SECRETARY

CBF:co

Ecnl.

McGarvey

St. George

owned rig on Virgin
pat. land well.

3-25-59

John W (Jack) McArthur
1326 W. No Temple SLC

drilled Bullock Well - his rig.

deepened to ^{T.D.} 1405' by

Don P. McGarvie, St. George
PO Box #475.

November 29, 1960

Black Gold and Mines Corp.
184 East 5th North
Provo, Utah

Attention: Ben H. Bullock, President

Re: Well No. Bullock #1, Sec. 22,
T. 41 S., R. 12 W., Washington
County, Utah

Gentlemen:

On July 29, 1960, our petroleum engineer visited the above mentioned well and found it still standing open. According to our information this well has never been plugged and abandoned.

We have been contacted by the Aetna Casualty and Surety Company, holders of the Bond for said well, and they desire to have this Bond terminated.

This well has been standing open since May 7, 1958, wherein, we feel a reasonable amount of time has passed and some arrangements should be made immediately for plugging this well. Therefore, you are hereby requested to contact this office regarding the plugging of said well and cleaning up of the location in order that we may release the Bond.

If we do not hear from you within the next two weeks we will turn this matter over to the Attorney General for necessary action.

Very truly yours,

OIL & GAS CONSERVATION COMMISSION

CLEON B. FRIGHT,
EXECUTIVE SECRETARY

CBF:avg

Provo, Utah
Nov. 30, 1960

Oil and Gas Conservation Commission
Cleo B. Feight
Executive Secretary
310 Newhouse Building
Salt Lake City 11 Utah

Dear Sir:

Monday Nov. 21, 1960 my son B. Vern Bullock and myself made a trip to our Virgin Oil Field and found the Bullock No. 1. well with a steel plate welded over the pipe as we had left it when the well was abandoned also there is a wooden box securely nailed together made of 2 inch plank and plank nailed on top of the box which covers the well. Every thing was just as we had left it.

The well was drilled to a depth of 1400 feet, we had oil and gas shows from the 87 foot depth to the bottom. We were in oil sand when the drilling ceased and from different Geologists that we had, it was estimated that we should go at least to the 2000 foot depth where we should have a chance of getting both oil and gas.

We are trying with plans to get the well deepened to the specified depth and by early spring we hope to be successful.

We cannot understand why your engineer should make such a report about the Bullock Well No. 1. This well is known all over the country because it is within a few feet of the State Highway that goes East and West, through the City of Virgin, Utah.

Kindly let me know what the next move is, as we firmly understood that we were complying with the law.

Sincerely

Black Gold and Mines Corporation

By Ben H. Bullock, President

184 East 5th North Street
Provo, Utah

December 5, 1960

Mr. Ben H. Bullock, President
Black Gold & Mines Corporation
184 East Fifth North
Provo, Utah

Re: Well No. Bullock 1, SE $\frac{1}{4}$ SW $\frac{1}{4}$ Section 22,
Township 41 South, Range 12 West, SLEM,
Washington County, Utah

Dear Mr. Bullock:

On July 29, 1960, when our engineer checked your lease he found three wells on the property approximately 100 feet apart in an east-west line. None of these wells were marked, so it was impossible to tell just what well was the Bullock No. 1. However, sour gas was escaping from the middle well. We suggest that you mark these wells as required by Rule C-7 of our rules and regulations, and take some action to prevent the gas from escaping.

Also, the bonding company has informed us that you have failed to pay the premium on your bond, and they would like to be released from liability. This can only be done by having these wells plugged or by renewal of the bond.

In view of the fact that no activity has taken place on this lease since early 1958, we feel that these wells should be plugged. We cannot allow these holes to remain open indefinitely, and it would appear that two years is a reasonable time in which to complete or to plug and abandon a well.

Please advise us as to what action you intend to take.

Yours very truly,

OIL & GAS CONSERVATION COMMISSION

CLEON B. FREIGHT
EXECUTIVE SECRETARY

CBF:co

March 22, 1961

Re: Black Gold & Mines Corp. - Well No.
Bullock 1, Virgin Townsite, Washington
County, Utah

**Honorable Walter L. Budge
Attorney General
Room 236, State Capitol Building
Salt Lake City 14**

**Attention: Mr. Ronald H. Boyce
Assistant Attorney General**

Dear Mr. Boyce:

Enclosed herewith is the Bullock File that I talked to you about. There are three wells located within 100 feet of each other on the Bullock Property. Each of these wells should be plugged and the locations cleaned up. However, the bonding company is only responsible for the Bullock No. 1 Well.

We are sorry to bother you with this problem, but I think we have waited long enough for Mr. Bullock to do something with respect to this well.

Yours very truly,

OIL & GAS CONSERVATION COMMISSION

**CLEON B. FREIGHT
EXECUTIVE SECRETARY**

**CBF:ee
Enclosure - File**

This is information with respect to the Ben Bullock
Wells in Washington County, Utah.

1. BLACK GOLD & MINING CORP. - Well No. Bullock #1,
30' FNL & 300' FWL of Sec. 22, T. 41 S., R. 12 W.,
Washington Co. Originally drilled by Ben Bullock
and abandoned 3-25-38 at a total depth of 185'.
Began re-working well 3-29-58 and shut it down on
5-7-58 at a total depth of 1402'.
2. UTAH GALENO OIL CORP. - SYNDICATE OIL & MINING CO.,
Well No. Bullock Surprise #1, SW $\frac{1}{4}$ SE $\frac{1}{4}$ of Sec. 22,
T. 41 S., R. 12 W., Washington Co. This well was
spudded in 12-13-53 and abandoned 3-4-54 at a
total depth of 480'.
3. UTAH GALENO OIL CORP. - SYNDICATE OIL & MINING CO.,
Well No. Bullock Surprise #2, SW $\frac{1}{4}$ SE $\frac{1}{4}$ of Sec. 22,
T. 41 S., R. 12 W., Washington Co. The rig was
skidded from Well No. Bullock Surprise #1, 100'
east to this well which was spudded in 3-6-54.
Operations were suspended indefinitely on approxi-
mately 4-17-54 at a total depth of 286'.

Cher
Service
Station

Mohawk
Cafe

MAIN Highway Through Virgin

(West St) Paved Road

CELLAR
Boarded

Pit 7 mounds of
Dirt


CELLAR
open 7 Pipe
in bottom leaking
gas

Pit 7 mounds of
Dirt

2" steel
Pipe w/ steel
plate welded
on top

Pit 7 mounds
of Dirt

(Mill St) Paved Road



OFFICE OF THE ATTORNEY GENERAL
STATE CAPITOL
SALT LAKE CITY 14, UTAH

March 27, 1961

Black, Gold & Mines Corporation
184 East 5th North
Provo, Utah

Gentlemen:

It has been called to our attention that three oil and gas wells drilled by you in the vicinity of Virgin, Utah, are in need of plugging due to gas leakage.

We therefore give you notice that unless action is commenced within 15 days to plug these wells, court action will be brought to compel you to do so.

Very truly yours

/s/ Ronald N. Boyce
RONALD N. BOYCE
Assistant Attorney General

RNB/jlt
cc/ Oil & Gas Commission

1961 6 24 MTC

X

OFFICE OF THE ATTORNEY GENERAL
STATE CAPITOL
SALT LAKE CITY 14, UTAH

April 3, 1961

C
O
P
Y

Black Gold and Mines Corp.
184 East 5th North
Provo, Utah
ATTN: Ben H. Bullock

Dear Mr. Bullock:

In accordance with your request of March 31, 1961, the Oil and Gas Commission agrees to your plugging all three wells in the virgin area at the depth of 25 feet.

In addition, I will grant you until May 1, 1961, to show accomplishment of this request before any court action is taken. I believe this should be adequate time.

Very truly yours,

RONALD N. BOYCE
Assistant Attorney General

RNB/jrg

This is information with respect to the Ben Bullock
Wells in Washington County, Utah.

1. BLACK GOLD & MINING CORP. - Well No. Bullock #1,
30' FNL & 300' FWL of Sec. 22, T. 41 S., R. 12 W.,
Washington Co. Originally drilled by Ben Bullock
and abandoned 3-25-38 at a total depth of 185'.
Began re-working well 3-29-58 and shut it down on
5-7-58 at a total depth of 1402'.
2. UTAH GALENO OIL CORP. - SYNDICATE OIL & MINING CO.,
Well No. Bullock Surprise #1, SW $\frac{1}{4}$ SE $\frac{1}{4}$ of Sec. 22,
T. 41 S., R. 12 W., Washington Co. This well was
spudded in 12-13-53 and abandoned 3-4-54 at a
total depth of 480'.
3. UTAH GALENO OIL CORP. - SYNDICATE OIL & MINING CO.,
Well No. Bullock Surprise #2, SW $\frac{1}{4}$ SE $\frac{1}{4}$ of Sec. 22,
T. 41 S., R. 12 W., Washington Co. The rig was
skidded from Well No. Bullock Surprise #1, 100'
east to this well which was spudded in 3-6-54.
Operations were suspended indefinitely on approxi-
mately 4-17-54 at a total depth of 286'.


Provo, Utah
May 4, 1961

Ronald N. Boyce
Assistant Attorney General
State Capitol
Salt Lake City, Utah

Dear Sir:

According to your instructions my son B. Vern Bullock the owner of the Virgin City property where the oil wells were drilled, plugged the three wells with cement to the depth of 25 feet as per your instructions.

Sincerely

A handwritten signature in cursive script that reads "Ben H. Bullock". The signature is written in dark ink and is positioned above a horizontal line.

Ben H. Bullock
184 East 5th, North Street
Provo, Utah



WALTER L. BUDGE
ATTORNEY GENERAL

THE STATE OF UTAH
OFFICE OF THE ATTORNEY GENERAL
SALT LAKE CITY

May 10, 1961


Cleon B. Feight
Executive Secretary
State Oil and Gas Commission
310 Newhouse Building
10 Exchange Place
Salt Lake City, Utah

Dear Cleon:

Enclosed is a letter I received
from Mr. Ben Bullock, indicating that the
Virgin Wells had been plugged.

I am also returning your file.

Very truly yours,


RONALD N. BOYCE
Assistant Attorney General

RNB/jrg

Encs.



WALTER L. BUDGE
ATTORNEY GENERAL

THE STATE OF UTAH
OFFICE OF THE ATTORNEY GENERAL
SALT LAKE CITY

May 12, 1961


Cleon B. Feight
Executive Secretary
State Oil and Gas Commission
310 Newhouse Building
10 Exchange Place
Salt Lake City, Utah

Dear Cleon:

I note in examining Rules D-1 through D-4 that the present rules of the Utah Oil and Gas Commission make no provision for a plugging operation on a well to be performed during the presence of a commission engineer. It would probably be helpful to add this a requirement to the present regulations.

With reference to the Black Gold-Virgin Wells, it would probably be helpful, in case we wanted to bring any action against Bullock for not properly plugging the wells, to give him notice that he must file an affidavit of plugging, setting out in detail the manner in which the well was plugged within 30 days of the operation being completed. This is required by Rule D-2.

Very truly yours,


RONALD N. BOYCE
Assistant Attorney General

RNB/jrg

Provo, Utah
May 17, 1961

Oil and Gas Conservation Commission
310 Newhouse Bldg.
10 Exchange Place
Salt Lake City, Utah

Gentlemen:

I am mailing a copy of letter I received from Ronald N. Boyce Assistant Attorney General in reference to the three oil wells drilled in Virgin City, Utah.

Copy Salt Lake City,
April 3, 1961

Dear Mr. Bullock:

In accordance with your request of March 31, 1961, the Oil and Gas Commission agrees to your plugging all three wells in the Virgin area at the depth of 25 feet.


In addition, I will grant you until May 1, 1961, to show accomplishment of this request before any court action is taken. I believe this should be adequate time.

Very truly yours,

RONALD N. BOYCE
Assistant Attorney General

May 4, 1961 I wrote Mr Boyce and informed him that the three wells had been plugged with cement to a depth of 25 feet as agreed to, by my son B. Vern Bullock owner of the property.

Sincerely



Ben H. Bullock
184 East 5th, North Street
Provo, Utah

May 23, 1961

Mr. Ben H. Bullock
184 East Fifth, North Street
Provo, Utah

Dear Mr. Bullock:

About two weeks ago we forwarded you some copies of
Form OGCC-2, Affidavit of Plugging and Abandonment, for
your completion and return.

Will you please advise us as to when we may expect to
receive same.

Yours very truly,

OIL & GAS CONSERVATION COMMISSION

CLEON B. FREIGHT
EXECUTIVE SECRETARY

CBF:co

July 19, 1961

Mr. Ben H. Bullock, President
Black Gold & Mines Corporation
184 East Fifth North
Provo, Utah

Re: Well No. Bullock 1, SE $\frac{1}{4}$ SW $\frac{1}{4}$, Section 22,
Township 41 South, Range 12 West, SLBM,
Washington County, Utah

Dear Mr. Bullock:

During the first week of July, 1961, I visited the locations of your three wells in the Virgin Field. It appeared that cement plugs had been placed in all three wells.

On May 23, 1961, we forwarded you some copies of our Form OGCC-2, Affidavit and Record of Abandonment and Plugging, for your completion and return. As of this date you have not furnished these forms to us as requested. The bond covering the Bullock No. 1 well cannot be released until this office is in receipt of said forms.

If the forms are not received by this office within the next two weeks, we will again turn this matter over to the Attorney General's Office to take action under your bond to insure that at least the Bullock No. 1 well is plugged as required by the rules and regulations of this Commission.

Yours very truly,

OIL & GAS CONSERVATION COMMISSION

CLEON B. FREIGHT
EXECUTIVE SECRETARY

CBF:cop

cc: Attorney General's Office
Attn: Ronald N. Boyce

X

OIL AND GAS CONSERVATION COMMISSION

AFFIDAVIT AND RECORD OF ABANDONMENT AND PLUGGING

PLUGGING METHODS AND PROCEDURE: --The method and procedure for plugging a well shall be as follows:

- (a) The bottom of the hole shall be filled to, or a bridge shall be placed at the top of each producing formation open to the well bore, and in either event, a cement plug not less than fifty (50) feet in length shall be placed immediately above each producing formation open to the well bore whenever possible.
- (b) A cement plug not less than fifty (50) feet in length shall be placed at approximately fifty (50) feet above and below all fresh water bearing strata.
- (c) A plug shall be placed at or near the surface of the ground in each hole.
- (d) The interval between plugs shall be filled with heavy mud-laden fluid.
- (e) The hole shall be plugged with heavy mud up to the base of the surface string at which point a plug of not less than fifty (50) feet of cement shall be placed.

Field or Pool Virgin Oil Field County Washington
 Lease Name Middle Well No. 1 Sec. 22 Twp. 41 R12 W.SLEM
 Date well was plugged: May 28th,, 1961.

Was the well plugged according to regulation of the Commission: Attorney General

Set out method used in plugging the well, the nature and quantities of materials used in plugging, size of plugs, location and extent (by depths) of the plugs of different materials, and the amount of casing left in hole, (giving size, top and bottom elevations of each section of abandoned casing).

Middle well No. 1.8 inch pipe, NW Cor Block 5, Lot 5 Plat B Virgin Townsite Survey
Used Burlap sack with stick and wire inserted in pipe to a depth of 28 feet, wadded tight,
wire held on top of casing by steel rod. Concrete prepared by Cement mixer and poured
into pipe.

Operator B. Vern Bullock
 Address 100 West 960 North
Provo, Utah

AFFIDAVIT

STATE OF UTAH

COUNTY OF Utah

Before me, the undersigned authority on this day personally appeared
B. Vern Bullock, known to me to be the person whose name is
 subscribed to the above instrument, who being by me duly sworn on oath states that
 he is authorized to make this report and has knowledge of the facts stated herein,
 and that said report is true and correct.

Subscribed and sworn to before me this 7th, day of August, 1961.

My Commission Expires: Aug. 17, 1962

Residing Provo, Utah

B. Vern Bullock
 NOTARY PUBLIC

INSTRUCTIONS: Complete this form in duplicate.

OIL AND GAS CONSERVATION COMMISSION

AFFIDAVIT AND RECORD OF ABANDONMENT AND PLUGGING

PLUGGING METHODS AND PROCEDURE: --The method and procedure for plugging a well shall be as follows:

- (a) The bottom of the hole shall be filled to, or a bridge shall be placed at the top of each producing formation open to the well bore, and in either event, a cement plug not less than fifty (50) feet in length shall be placed immediately above each producing formation open to the well bore whenever possible,
- (b) A cement plug not less than fifty (50) feet in length shall be placed at approximately fifty (50) feet above and below all fresh water bearing strata.
- (c) A plug shall be placed at or near the surface of the ground in each hole.
- (d) The interval between plugs shall be filled with heavy mud-laden fluid.
- (e) The hole shall be plugged with heavy mud up to the base of the surface string at which point a plug of not less than fifty (50) feet of cement shall be placed.

Field or Pool Virgin Oil Field County Washington
Lease Name Bullock Well No. 1 Sec. 22 Twp. 41 R. 12 W SLB M
Date well was plugged: May 28th,, 1961.

Was the well plugged according to regulation of the Commission: Attorney General

Set out method used in plugging the well, the nature and quantities of materials used in plugging, size of plugs, location and extent (by depths) of the plugs of different materials, and the amount of casing left in hole, (giving size, top and bottom elevations of each section of abandoned casing).

Bullock well No. 1. 10 inch pipe, NW Cor. Lot 4, Block 5, plat B. Virgin Townsite Survey
Used Burlap sack with stick and wire inserted in the pipe to a depth of 28 feet, wadded
tight, held on top of casing by steel rod, Concrete prepared by Cement mixer and poured
into pipe.

Operator B. Vern Bullock
Address 100 West 960 North,
Provo, Utah

AFFIDAVIT

STATE OF UTAH

COUNTY OF Utah

Before me, the undersigned authority on this day personally appeared B. Vern Bullock, known to me to be the person whose name is subscribed to the above instrument, who being by me duly sworn on oath states that he is authorized to make this report and has knowledge of the facts stated herein, and that said report is true and correct.

Subscribed and sworn to before me this 7th, day of August, 1961.

My Commission Expires: Aug. 17, 1962

Residing Provo, Utah

Don H. Bullock
NOTARY PUBLIC

INSTRUCTIONS: Complete this form in duplicate.

OIL AND GAS CONSERVATION COMMISSION

AFFIDAVIT AND RECORD OF ABANDONMENT AND PLUGGING

PLUGGING METHODS AND PROCEDURE: --The method and procedure for plugging a well shall be as follows:

- (a) The bottom of the hole shall be filled to, or a bridge shall be placed at the top of each producing formation open to the well bore, and in either event, a cement plug not less than fifty (50) feet in length shall be placed immediately above each producing formation open to the well bore whenever possible,
- (b) A cement plug not less than fifty (50) feet in length shall be placed at approximately fifty (50) feet above and below all fresh water bearing strata.
- (c) A plug shall be placed at or near the surface of the ground in each hole.
- (d) The interval between plugs shall be filled with heavy mud-laden fluid.
- (e) The hole shall be plugged with heavy mud up to the base of the surface string at which point a plug of not less than fifty (50) feet of cement shall be placed.

Field or Pool Virgin Oil Field County Washington
 Lease Name B & B Well No. 1 Sec. 22 Twp. 41 R. 12 W SLEM
 Date well was plugged: May 28th,, 19 61.

Was the well plugged according to regulation of the Commission: Attorney General

Set out method used in plugging the well, the nature and quantities of materials used in plugging, size of plugs, location and extent (by depths) of the plugs of different materials, and the amount of casing left in hole, (giving size, top and bottom elevations of each section of abandoned casing).

B & B well No. 1, 10 inch pipe, NE Cor. Block 5, Lot 5, Plat B. Virgin Townsite Survey.
Middle well, 8 inch pipe, NW Cor. Lot 5, Block 5, Plat B. Virgin Townsite Survey.
Bullock Well No. 1, 10 inch pipe, NW Cor. Lot 4, Block 5, Plat B. Virgin Townsite Survey.
Used Burlap sack with stick and wire inserted in pipe to a depth of 20 feet, wadded tight
wire held on top of casing by steel rod. Concrete prepared by Cement mixer and poured
into pipe.

Operator B Vern Bullock
 Address 100 West 960 North
Provo, Utah.

AFFIDAVIT

STATE OF UTAH

COUNTY OF Utah

Before me, the undersigned authority on this day personally appeared B. Vern Bullock, known to me to be the person whose name is subscribed to the above instrument, who being by me duly sworn on oath states that he is authorized to make this report and has knowledge of the facts stated herein, and that said report is true and correct.

Subscribed and sworn to before me this 7th, day of August, 1961.

My Commission Expires: Aug 17, 1962

Residing at Provo, Utah

Bern Bullock
 NOTARY PUBLIC

INSTRUCTIONS: Complete this form in duplicate.

August 11, 1961

The Aetna Casualty & Surety Co.
Ed D. Smith & Sons
425 South Main Street
Salt Lake City, Utah

Re: Bond No. 46 S 2925 covering
Ben H. Bullock's Well No.
Bullock #1, Sec. 22, T. 41 S.,
R. 12 W., Washington County,
Utah

Gentlemen:

During the first week of July, 1961, Mr. Cleon B. Feight inspected the well location for the above mentioned well and found that the well was satisfactorily plugged and abandoned in accordance with the rules and regulations of this Commission.

Therefore, liability under Bond No. 46 S 2925 is hereby released.

Very truly yours,

OIL & GAS CONSERVATION COMMISSION

CLEON B. FEIGHT,
EXECUTIVE SECRETARY

CBF:avg

cc: Mr. Ben H. Bullock

30' FNL 300' FWL
(SEE POST-IT) #1

PUTS THE WELL IN THE
NWNW QQ.

COMPUTER STATES
S-SE #2?

???

PLEASE HELP!

BRUSE

9/11-87

✓ 8-25-87

✓

this well is located
in ~~SW~~ SE 99.

127

9-11-87

